

LUBRAL M4T SAE 15W-50 API SL/JASO MA2

SYNTHETIC OIL FOR 4-STROKE ENGINES

DESCRIPTION

LUBRAL M4T SAE 15W-50 API SL/JASO MA2 is a Synthetic oil, formulated for the lubrication of motorcycles with 4-stroke gasoline engines with gearbox and clutches immersed in oil. It provides the desired friction performance that motorcycles need to prevent slippage in the wet clutch.

BENEFITS

- Control of sludge and deposits.
- Control of wear caused by the high temperatures and excessive friction to which engines of this type are subjected.

- Anti-rust protection to minimize viscosity increase and the formation of sludge, lacquers and varnishes.
- Provides higher friction performance.

SPECIFICATIONS

- API SL
- JASO MA2 (T903:2016)

APPLICATIONS

LUBRAL M4T SAE 20W-50 API SN/JASO MA2 oil is recommended for the service of 4-stroke gasoline engines of motorcycles with gearbox and clutches (clutch), immersed in oil.

CHARACTERISTICS

TESTS	TEST METHOD	TYPICAL VALUE
SAE Grade	J300	15W-50
Appearance	Visual	Bright
Color	ASTM D1500	2.5
Density @ 20°C, g/cm ³	ASTM D4052	0.85
Kinematic Viscosity @ 40 °C, cSt	ASTM D445	123
Kinematic Viscosity @ 100 °C, cSt	ASTM D445	19
Viscosity Index	ASTM D2270	174
Flash Point COC, °C	ASTM D92	225
Pour Point, °C, max	ASTM D97	-33
Cold Cracking Simulator CSC, cP @-20°C, max	ASTM D5293	7000

Typical Characteristics are those obtained with normal tolerance of production and no constitute a specification. Variations that do not affect the yield product during the normal manufacturing and on different mixing locations are expected. Information contained in this document is held to changes without previous advisement. The availability of the products could vary depending on the location. For further information, contact venta@lubral.com