

# LUBRAL SUPER RACING PRO SAE 10W-30 API SN PLUS

## SYNTHETIC MULTIGRADE OIL

### DESCRIPTION

LUBRAL SUPER RACING PRO SAE 10W-30 API SN PLUS is a high-quality synthetic oil specially designed for modern engines. Made with synthetic bases and a state-of-the-art additive package that provides the engine with excellent protection against wear and oxidation, allowing longer drainage periods. Thanks to its anti-friction technology, it provides a long engineering life and contributes to fuel savings, as well as reducing CO2 emissions. Enhanced with carefully balanced chemistry that prevents LSPI damage in TGDl and GDI engines.

### BENEFITS

- Protects modern TGDl and GDI engines against damage caused by LSPI (Low Speed Pre-Ignition).
- Fuel savings and reduction of harmful emissions into the atmosphere.
- Contains superior quality detergents and dispersants, preventing the accumulation of sludge and deposits in the engine.
- Synthetic technology that allows extended drain periods.
- Excellent fluidity at low temperatures facilitating starting in cold climates.
- Anti-friction technology that provides protection against metal-to-metal wear.

### SPECIFICATIONS

- API SN Plus
- API SN
- ILSAC GF-5
- Resource Conserving

### APPLICATIONS

LUBRAL SUPER RACING PRO SAE 10W-30 API SN PLUS is recommended for the service of gasoline engines of vehicles of the year 2020 and earlier with additional protection against pre-ignition at low speeds.

Consult your vehicle manual for the correct viscosity grade.

# LUBRAL SUPER RACING PRO SAE 10W-30 API SN PLUS

## SYNTHETIC MULTIGRADE OIL

### CHARACTERISTICS

TESTS	ASTM METHOD	TYPICAL VALUE
Grado SAE	<b>SAE J300</b>	10W-30
Color	ASTM D1500	2.5
Density @20°C, g/ml	ASTM D4052	0.85
Appearance	Visual	Bright
Kinematic viscosity @ 40°C, cSt	ASTM D445	73
Kinematic viscosity @ 100°C, cSt	ASTM D445	10
Viscosity index	ASTM D2270	160
Foam Tendency, ml, max.	ASTM D892	
Sequence I		10/0
Sequence II		50/0
Sequence III		10/0
TBN	ASTM D2896	7.5
CCS, Cp @-25°C	ASTM D5293	4500
Flash point, °C	ASTM D92	240
Pour point, °C, max.	ASTM D97	-36

Typical Characteristics are those obtained with normal tolerance of production and no constitute a specification. Variations that do not affect the yield product during the normal manufacturing and on different mixing locations are expected.

Information contained in this document is held to changes without previous advisement. The availability of the products could vary depending on the location. For further information, contact [venta@lubral.com](mailto:venta@lubral.com)