

LUBRAL SUPER RACING PRO SAE 10W-40 API SN PLUS

GASOLINE ENGINE SYNTHETIC MULTIGRADE OIL

DESCRIPTION

LUBRAL SUPER RACING PRO SAE 10W-40 API SN PLUS is a high quality synthetic oil, specially designed for modern engines. It is made with synthetic bases and a state-of-the-art additive package that provides the engine with maximum protection against wear and oxidation, allowing longer drain periods. Thanks to its anti-friction technology, it provides long engine life and contributes to fuel economy and lower CO2 emissions. Enhanced with carefully balanced chemistry that prevents damage caused by LSPI in TGD and GD engines.

BENEFITS

- Protects modern TGD and GD engines against damage caused by LSPI (Low Speed Pre-Ignition).
- Saves fuel and reduces harmful emissions to the atmosphere.
- Contains superior detergents and dispersants, preventing the accumulation of sludge and deposits in the engine.

CHARACTERISTICS

TESTS	TEST METHOD	TYPICAL VALUE
SAE Grade	J300	10W-40
Appearance	Visual	Bright
Color	ASTM D1500	2.0
Density@ 20°C, g/cm ³	ASTM D4052	0.84
Kinematic viscosity @40°C, cSt	ASTM D445	92
Kinematic viscosity @100°C, cSt	ASTM D445	14
Viscosity Index	ASTM D2270	140
Flash point COC, °C	ASTM D92	246
Pour point, °C, max	ASTM D97	-36
Cold cracking simulation CCS, cP @-25°C	ASTM D5293	5800
TBN, mg KOH/g	ASTM D2896	7.5
Foam Tendency ml, max.	ASTM D892	
Sequence I		10/0
Sequence II		50/0
Sequence III		10/0

- Synthetic technology that allows extended drain periods.
- Excellent fluidity at low temperatures, facilitating starting in cold climates.
- Anti-friction technology that provides protection against metal-to-metal wear.

SPECIFICATIONS

- API SN Plus
- API SN

APPLICATIONS

LUBRAL SUPER RACING PRO SAE 10W-40 API SN PLUS is recommended for gasoline engines of 2020 and earlier vehicles with additional protection against pre-ignition at low speeds. Consult your vehicle's manual for the correct viscosity grade.

Typical Characteristics are those obtained with normal tolerance of production and no constitute a specification. Variations that do not affect the yield product during the normal manufacturing and on different mixing locations are expected. Information contained in this document is held to changes without previous advisement. The availability of the products could vary depending on the location. For further information, contact venta@lubral.com