

# LUBRAL SUPER RACING X SAE 5W-30 API SN PLUS

## GASOLINE ENGINE MULTIGRADE OIL

### DESCRIPTION

Lubral Super Racing X SAE 5W-30 API SN PLUS oil is made with highly refined paraffinic bases combined with last generation additive packages that provide engines maximum protection and excellent performance under different operating conditions. Thanks to its technology, it provides long life to engine components, contributes to fuel economy and reduces CO<sub>2</sub> emissions. Its carefully balanced formula prevents damage caused by the LSPI phenomenon in TGDI and GDI engines. Satisfies API SN Plus and ILSAC GF-5 requirements.

### BENEFITS

- Extends engine life.
- Protects modern TGDI and GDI engines against the LSPI (Low Speed Pre-Ignition) phenomenon.

- Fuel savings and reduction of harmful emissions into the atmosphere.
- Contains superior quality detergents and dispersants, preventing the accumulation of sludge and deposits in the engine.
- Excellent fluidity at low temperatures facilitating cold weather starting.

### SPECIFICATIONS

- API SN Plus
- API SN
- ILSAC GF-5
- API Resource Conserving
- Ford WSS-M2C945-A
- Ford WSS-M2C945-A

### APPLICATIONS

Recommended for late model and prior year gasoline engine service with added protection against preignition at low speeds. Consult your vehicle manual for the correct viscosity grade.

# LUBRAL SUPER RACING X SAE 5W-30 API SN PLUS

GASOLINE ENGINE MULTIGRADE OIL

## CHARACTERISTICS

TESTS	TEST METHOD	TYPICAL VALUE
Viscosity grade SAE	SAE J300	5W-30
Clasification API		SN PLUS
Color	ASTM D1500	2.5
Density @20 °C, g/mL	ASTM D4052	0.85
Kinematic Viscosity @40 °C, cSt	ASTM D445	63
Kinematic Viscosity @100 °C, cSt	ASTM D445	10
Viscosity Index	ASTM D2270	144
Flash point COC, °C	ASTM D92	225
Pour point, °C	ASTM D97	-40
TBN	ASTM D2896	7.5
Cold cracking simulation, Cp @-30°C, cP	ASTM D5293	6000
Foaming Tendency / Stability ml, max.	ASTM D892	
Sequence I		10/0
Sequence II		50/0
Sequence III		10/0

Typical Characteristics are those obtained with normal tolerance of production and no constitute a specification. Variations that do not affect the yield product during the normal manufacturing and on different mixing locations are expected.

Information contained in this document is held to changes without previous advisement. The availability of the products could vary depending on the location. For further information, contact [venta@lubral.com](mailto:venta@lubral.com)