

LUBRAL SUPER RACING X SAE 15W-40

API SN PLUS

MULTIGRADE MINERAL OIL

DESCRIPTION

LUBRAL SUPER RACING X SAE 15W40 API SN PLUS oil is a carefully formulated lubricant with high-tech additives to obtain great performance in gasoline engines, even under extreme operating conditions. Its formulation has a low ash content, which improves combustion and increases the life of the engine. Enhanced with friction modifiers that help minimize the occurrence of Low Speed Preignition (LSPI).

BENEFITS

- High viscosity index, ensuring an appropriate viscosity grade under extreme temperature conditions.
- Protects modern TGD engines.
- Excellent fluidity at low temperatures facilitating cold weather starting.
- Low ash formation.

APPLICATIONS

LUBRAL SUPER RACING X SAE 15W-40 API SN PLUS oil is recommended for the service of gasoline engines of vehicles of the year 2020 and prior years with additional protection against pre-ignition at low speeds.

This oil meets the API SN PLUS service classification.

CHARACTERISTICS

TESTS	TEST METHOD	TYPICAL VALUE
Viscosity grade SAE	SAE J300	15W-40
Clasificación API		SN PLUS
Color	ASTM D1500	2.5
Density @20 °C, g/mL	ASTM D4052	0.86
Kinematic Viscosity @40 °C, cSt	ASTM D445	105
Kinematic Viscosity @100 °C, cSt	ASTM D445	14.2
Viscosity Index	ASTM D2270	138
Flash point COC, °C	ASTM D92	232
Pour point, °C, máx	ASTM D97	-24
TBN	ASTM D2896	7.5
Cold cracking simulation, Cp @-20°C, cP	ASTM D5293	5600
Foaming Tendency / Stability ml, max.	ASTM D892	
Sequence I		10/0
Sequence II		50/0
Sequence III		10/0

Typical Characteristics are those obtained with normal tolerance of production and do not constitute a specification. Variations that do not affect the yield product during the normal manufacturing and on different mixing locations are expected.

Information contained in this document is held to changes without previous advisement. The availability of the products could vary depending on the location. For further information, contact venta@lubral.com