

# LUBRAL SUPER RACING X SAE 25W-60

## API SN PLUS

### MULTIGRADE MINERAL OIL

#### DESCRIPTION

LUBRAL SUPER RACING X SAE 25W-60 API SN PLUS oil is a lubricant formulated with high-tech additives to obtain maximum performance in gasoline engines, even under extreme operating conditions. Its formulation has a low ash content, which improves combustion and increases the life of the engine. Enhanced with friction modifiers that help minimize the occurrence of Low Speed Preignition (LSPI). Satisfies API SN PLUS specification.

#### BENEFITS

- Helps extend engine life.
- High viscosity index, ensuring complete protection at low and high temperatures.

#### CHARACTERISTICS

- Protects modern TGDl and GDI engines against the LSPI (Low Speed Pre-Ignition) phenomenon.
- Contains superior quality detergents and dispersants, preventing the accumulation of sludge and deposits in the engine.
- Low ash formation.

#### APPLICATIONS

LUBRAL SUPER RACING X SAE 25W-60 API SN PLUS oil is recommended for the service of gasoline engines of vehicles of the year 2020 and prior years with additional protection against pre-ignition at low speeds.

Consult your vehicle manual for the correct viscosity grade.

TESTS	TEST METHOD	TYPICAL VALUE
Viscosity grade SAE	SAE J300	25W-60
Clasificación API		SN PLUS
Color	ASTM D1500	3
Density @20 °C, g/mL	ASTM D4052	0.88
Kinematic Viscosity @40 °C, cSt	ASTM D445	237
Kinematic Viscosity @100 °C, cSt	ASTM D445	22
Viscosity Index	ASTM D2270	118
Flash point COC, °C	ASTM D92	220
Pour point, °C, máx	ASTM D97	-18
TBN	ASTM D2896	7.5
Cold cracking simulation, Cp @-10°C, cP	ASTM D5293	7000
Foaming Tendency / Stability ml, max.	ASTM D892	
Sequence I		10/0
Sequence II		50/0
Sequence III		10/0

Typical Characteristics are those obtained with normal tolerance of production and no constitute a specification. Variations that do not affect the yield product during the normal manufacturing and on different mixing locations are expected.

Information contained in this document is held to changes without previous advisement. The availability of the products could vary depending on the location. For further information, contact [venta@lubral.com](mailto:venta@lubral.com)