

LUBRAL RACING SAE 25W-50 API SL

GASOLINE ENGINE MULTIGRADE OIL

DESCRIPTION

LUBRAL RACING SAE 25W-50 API SL oil is developed with a special formula prepared with high technology.

Due to the composition of high-quality basic ingredients and qualified additives that provide the mixture with special characteristics, a versatile product is obtained as a result.

BENEFITS

- Increases engine power.
- Stabilizes oil leaks by interacting with seals and retainers.

- It reduces the pollution of the environment by reducing the emission of gases.
- Optimal lubrication under extreme temperature conditions.

APPLICATIONS

Recommended for the service of gasoline engines of vehicles of the year 2004 and previous. Satisfies API SL service classification. Its application is recommended in public or private service gasoline vehicle engines with 100,000 travel kilometers or more.

CHARACTERISTICS

TEST	TEST METHOD	TYPICAL VALUE
SAE Grade		25W-50
API classification		SL
Color	ASTM D1500	3.0
Density @20°C, g/ml	ASTM D4052	0.88
Flash point COC, °C, mín	ASTM D92	225
Kinematic viscosity @ 100°C, cSt	ASTM D445	18
Kinematic viscosity @ 40°C, cSt	ASTM D445	173
Viscosity index	ASTM D2270	124
Cold start simulation, Cp @-35°C	ASTM D5293	13000
Pour point, °C	ASTM D97	-21
TBN, mg KOH/g	ASTM D2896	6.5
Foam tendency, ml máx.	ASTM D892	
Sequence I		10/0
Sequence II		50/0
Sequence III		10/0

Typical Characteristics are those obtained with normal tolerance of production and no constitute a specification. Variations, that do not affect the yield product during the normal manufacturing and on different mixing locations are expected.

Information contained in this document is held to changes without previous advisement. The availability of the products could vary depending on the location. For further information, contact venta@lubral.com.