

LUBRAL DUO TEMP 96%

DESCRIPTION

The LUBRAL DUO TEMP 96% is a formulation based on Ethylene glycol with adequate performance characteristics for cooling systems of combustion engines that are made up of metals or alloys of the type Aluminum, Steel, Copper, Iron and Bronze.

In its formulation, the antifreeze / coolant contains anti-corrosion, anti-rust and metal passivating additives that protect against oxidation and corrosion of the cooling systems, avoiding leaks in the radiator and damage to the water pump and the thermostat.

BENEFITS

- Maximum protection under low and high temperatures.
- Maximum protection against rust and corrosion.

- Good protection in long change periods.
- Excellent protection in aluminum, steel, copper, bronze, iron, hoses, rubber and seals.

APPLICATIONS

The LUBRAL DUO TEMP 96% is recommended for most domestic and imported automotive vehicles, passenger cars, light duty trucks, construction equipment, and stationary-type installations.

Use clean softened water, preferably distilled or deionized water. Mining wastewater, seawater or industrial waste should not be used.

Meets or exceeds SAE J-1034 and ASTM D3306 specifications for Ethylene Glycol-based machine antifreeze.

CHARACTERISTICS

TESTS	TEST METHOD	TYPICAL VALUE
Color	Visual	Fluorescent yellow
Appearance	Visual	Bright
Density @ 20°C	ASTM D1122	1.1
Freezing temperature, °C, 50 % in distilled water	ASTM D1177	-37
Boiling temperature without dilution, °C	-	160
Boiling temperature, °C, 50 % in distilled water (atmospheric pressure)	ASTM D1120	107
Boiling temperature, °C, 50 % in distilled water (15 psi)	ASTM D1120	130
pH, 50% in distilled water	ASTM D1287	10
Water, % weight	ASTM D1123	3.0
Alkaline reserve, ml	ASTM D1121	10

Typical Characteristics are those obtained with normal tolerance of production and no constitute a specification. Variations, that do not affect the yield product during the normal manufacturing and on different mixing locations are expected.

Information contained in this document is held to changes without previous advisement. The availability of the products could vary depending on the location. For further information, contact venta@lubral.com.