

LUBRAL DUO TEMP 35%

DESCRIPTION

PRE-MIXED DUO TEMP ANTI FREEZE 35% has an antifreeze antiboil component such as Ethylene Glycol that raises the boiling point of the water and lowers the freezing point. Decreases the corrosion rate in coolant systems constituted by metals or alloys of the type aluminum, steel, copper, iron and bronze.

BENEFITS

- Outstanding protection at low and high temperatures.
- Outstanding protection against oxidation and corrosion.
- Excellent protection in long periods of change.
- Excellent protection in aluminum, steel, copper, brass, iron, hoses, rubber and seals.

APPLICATIONS

Recommended for most domestic and imported automotive vehicles, passenger cars, light duty trucks, etc.

CHARACTERISTICS

TESTS	TEST METHOD	TYPICAL VALUES
Appearance	Visual	Clear and Bright
Color	Visual	Yellow
Density @ 20°C	ASTM D-4052	1.05
Freeze point. °C	ASTM D-1177	-18
Boiling point, °C (15 psi)	ASTM D-1120	126
Boiling point, °C (atmospheric pressure)	ASTM D-1120	104
pH @ 100%	ASTM D-1287	8.5
Water content, %	ASTM D-1123	63.4
Corrosion protection	ASTM D-1384	Pass

Typical Characteristics are those obtained with normal tolerance of production and no constitute a specification. Variations, that do not affect the yield product during the normal manufacturing and on different mixing locations are expected.

Information contained in this document is held to changes without previous advisement. The availability of the products could vary depending on the location. For further information, contact venta@lubral.com