

LUBRAL TRANS SAE 85W-140 API GL-1

DESCRIPTION

Lubricating oil formulated with high quality mineral base oils and antifoam additives that provide adequate characteristics to perform in transmissions where an API GL-1 quality oil is required.

BENEFITS

- Resistance to foaming.
- Repellency to the emulsion with water.
- High viscosity index.
- Moderate resistance to oxidation.
- Good film resistance.

APPLICATIONS

It is recommended for use in light to moderate duty manual transmissions of automobiles, vans, and trucks and in general where the use of an API GL-1 grade STD transmission oil is specified.

CHARACTERISTICS

TESTS	TEST METHOD	TYPICAL VALUE
SAE Viscosity Grade	J306	85W-140
Color	ASTM D1500	3.5
Appearance	Visual	Bright
Density, @20°C, g/cm ³	ASTM D4052	0.89
Kinematic Viscosity @ 40°C, cSt	ASTM D445	380
Kinematic Viscosity @ 100°C, cSt	ASTM D445	29
Viscosity Index	ASTM D2270	105

Typical Characteristics are those obtained with normal tolerance of production and no constitute a specification. Variations, that do not affect the yield product during the normal manufacturing and on different mixing locations are expected. Information contained in this document is held to changes without previous advisement. The availability of the products could vary depending on the location. For further information, contact venta@lubral.com