

LUBRAL AXTRAN SAE 90 API GL-4

DESCRIPTION

Multipurpose moderate to heavy duty automotive gear lubricant. Made with paraffinic bases and additives that provide excellent extreme pressure properties, wear resistance, resistance against foaming, corrosion and oxidation. Developed to meet the most rigorous service conditions in manual transmissions, differentials, axles, final drives, steering gearboxes of automobiles, passenger trucks, cargo trucks, fleets, agricultural equipment, etc.

BENEFITS

- Protection against oxidation at high temperatures.

- Protects gears against scratches.
- Shock or impact loads decrease.
- High protection against rust and corrosion.
- Resistance to foaming.
- Reduces wear.
- Resistance to corrosion in the presence of water.

APPLICATIONS

It is recommended for the lubrication of manual transmissions, differentials, steering gearboxes, semi-automatic transmission gears, gearboxes, drive shafts, final drives and in general, where a gear oil that meets the quality is required. API GL-4. Light and heavy transport and commercial vehicles.

CHARACTERISTICS

TESTS	TEST METHOD	TYPICAL VALUE
Viscosity Grade SAE	-	90
Color	ASTM D1500	3.0
Appearance	Visual	Brilliant
Density @20°C, g/ml	ASTM D1298	0.89
Linematic Viscosity @ 100 °C, cSt	ASTM D445	18.5
Viscosity Index	ASTM D2270	90
Flash Point COC, °C	ASTM D92	235
Resistance to rust formation	ASTM D665	Pass
Foaming, ml/min, máx.	ASTM D892	
Sequence I		20/0
Sequence II		50/0
Sequence III		20/0

Las Propiedades Típicas son aquellas obtenidas con tolerancia normal de producción y no constituyen una especificación. Se esperan variaciones que no afectan el rendimiento del producto durante la fabricación normal y en diferentes lugares de mezclado.

La información contenida en este documento está sujeta a cambios sin previo aviso. La disponibilidad de los productos puede variar dependiendo de la localidad. Para obtener más información, nos puede contactar en venta@lubral.com