

## LUBRAL ATF TYPE FA

### DESCRIPTION

Lubricating fluid made from highly refined paraffinic base oils and additives that give it adequate antioxidant and anti-wear characteristics, where an oil with GM Type A Suffix A classification is required.

### BENEFITS

- Excellent antioxidant protection.

- Excellent wear protection.
- Excellent anticorrosive protection.

### APPLICATIONS

Recommended for application in automatic transmissions that require an oil that meets the requirements of GM Type A Suffix A.

### CHARACTERISTICS

TESTS	TEST METHOD	TYPICAL VALUE
Color	Visual	Red
Appearance	Visual	Bright
Density @20°C, g/ml	ASTM D1298	0.88
Kinematic Viscosity @40°C, cSt	ASTM D445	47.5
Kinematic Viscosity @100 °C, cSt	ASTM D445	8
Viscosity Index	ASTM D2270	140
Flash Point COC, °C	ASTM D92	180
Rust formation resistance	ASTM D665	Pass
Foam Tendencies, ml, max.	ASTM D892	
Sequence I		20/0
Sequence II		50/0
Sequence III		20/0

Typical Characteristics are those obtained with normal tolerance of production and no constitute a specification. Variations that do not affect the yield product during the normal manufacturing and on different mixing locations are expected. Information contained in this document is held to changes without previous advisement. The availability of the products could vary depending on the location. For further information, contact [venta@lubral.com](mailto:venta@lubral.com)