

UNIVERSAL SYNTHETIC ATF

AUTOMATIC TRANSMISSION FLUID

DESCRIPTION

Synthetic lubricant fluid for automatic transmissions, formulated to be used in most automatic transmissions, Asian, European and American vehicles. It is elaborated with synthetic base oils and additives of last generation to ensure the correct operation and performance.

BENEFITS

- Superior oxidation control.
- Superior friction control, as required by Dexron® specifications, which translates into satisfactory operation over the life of the vehicle.
- Superior antiwear protection.
- Superior anti-shudder performance and durability.
- Superior clutch-shifting characteristics.
- Performance demonstrated in standard industry and OEM test.

APPLICATIONS

Suitable for use in transmissions that require

✓ Aisin Warner AW-1	✓ Honda ATF-Z1	✓ MERCON®
✓ Allison C-4	✓ Honda Premium	✓ MERCON®SP
✓ Audi G 052 025-A2	✓ Hyundai NWS-9638	✓ Mitsubishi Diamond SP-II
✓ Audi G-052-161-A1	✓ Jaguar ZF 5HP24	✓ Mitsubishi Diamond SP-III
✓ Audi G 052 162-A1	✓ Jaguar LT1141	✓ NAG 1 (Jeep Cherokee)
✓ Audi G 055 025-A2	✓ Jaguar JLM20238	✓ NAG 1 (Chrysler)
✓ BMW 5HP24	✓ Jaguar ATF 3403-M115	✓ Shell 3403
✓ BMW 5HP30	✓ JASO 1A-02	✓ Shell LA2634
✓ BMW 7045E	✓ JASO 2A-02	✓ Subaru ATF
✓ BMW LA2634	✓ JWS 3324	✓ Texaco 7045-E
✓ BMW LT71141	✓ JWS 3309	✓ Texaco ETL-8072B
✓ BMW ZF 5HP18FL	✓ KIA SP-II	✓ Toyota T-III
✓ Caterpillar TO-2	✓ KIA SP-III	✓ Toyota T-IV
✓ Chrysler ATF +®	✓ MAN 339 Type Z-1 and V-1	✓ Toyota WS
✓ Chrysler ATF +2®	✓ MAN 339 Type Z-2 and V-2	✓ Voith 55.6335
✓ Chrysler ATF +3®	✓ MAN 339F	✓ Voith 55.6336.32 (G1363)
✓ Chrysler ATF +4®	✓ Mazda ATF-III	✓ Voith Turbo
✓ DEXRON®	✓ Mazda M-V	✓ Volvo 97340
✓ DEXRON®-IID	✓ MB223.2	✓ VW TL52162
✓ DEXRON®-IIE	✓ MB236.2	✓ VW G-053 025-A2
✓ DEXRON®-III	✓ MB236.1	✓ VW G-053 162-A1
✓ DEXRON®-III G	✓ MB236.10	✓ ZF Ecomat
✓ DEXRON®-IIIH	✓ MB236.5	✓ ZF TE-ML 02F
✓ Esso LT 71141	✓ MB236.6	✓ ZF TE-ML 03D
✓ Ford M2C138CJ	✓ MB236.7	✓ ZF TE-ML 04D
✓ Ford M2C166H	✓ MB236.8	✓ ZF TE-ML 09
✓ GM99861695 (Aisin AW)	✓ MB236.9	✓ ZF TE-ML 11A
✓ GM TASA	✓ MB236.11	✓ ZF TE-ML 14A,B,C
✓ ZF TE-ML 17C		✓ ZF TE-ML 16L

Not recommended for:

Allison TES-295	Allison TES-389	Ford Type F/G	DEXRON® VI	CVT's
-----------------	-----------------	---------------	------------	-------

UNIVERSAL SYNTHETIC ATF
AUTOMATIC TRANSMISSION FLUID**CHARACTERISTICS**

TESTS	TEST METHOD	TYPICAL VALUE
Color	Visual	Red
Appearance	Visual	Clear and bright
Density @20°C, g/cm ³	ASTM D4052	0.87
Kinematic Viscosity @40°C, cSt	ASTM D445	35
Kinematic Viscosity @100 °C, cSt	ASTM D445	7.2
Viscosity Index	ASTM D2270	160
Flash Point COC, °C	ASTM D92	200
Rust formation resistance	ASTM D665	Pass

Typical Characteristics are those obtained with normal tolerance of production and no constitute a specification. Variations that do not affect the yield product during the normal manufacturing and on different mixing locations are expected.

Information contained in this document is held to changes without previous advisement. The availability of the products could vary depending on the location. For further information, contact venta@lubral.com