

LUBRAL ATF DXIII

AUTOMATIC TRANSMISSION FLUID

DESCRIPTION

Lubricating fluid made with refined base oil and additives that provide characteristics against oxidation, rust, corrosion, wear and formation of sludge in its performance in automatic transmissions.

BENEFITS

- Deposit control.
- High viscosity index.
- Resistance to oxidation and corrosion.
- Resistance to foaming.

- Good cleaning control.
- Good shear stability.
- Adequate seal performance.

APPLICATIONS

It is used in automatic transmissions for automobiles, trucks, construction equipment, agricultural equipment, marine equipment, and hydraulic systems that require a light to moderate duty automatic transmission fluid. It is used in automatic transmissions that require the Dexron III type.

CHARACTERISTICS

TESTS	TEST METHOD	TYPICAL VALUE
Color	Visual	Amber
Appearance	Visual	Bright
Density @20°C, g/ml	ASTM D1298	0.87
Kinematic Viscosity @40°C, cSt	ASTM D445	40
Kinematic Viscosity @100°C, cSt	ASTM D445	7.5
Viscosity Index	ASTM D2270	162
Flash point, °C	ASTM D92	180

Typical Characteristics are those obtained with normal tolerance of production and no constitute a specification. Variations that do not affect the yield product during the normal manufacturing and on different mixing locations are expected. Information contained in this document is held to changes without previous advisement. The availability of the products could vary depending on the location. For further information, contact venta@lubral.com