

ATF DX III

AUTOMATIC TRANSMISSION FLUID

DESCRIPTION

Automatic Transmission Lubricant Fluid formulated with high refined base oils and additives to warranty the correct operation and performance of the transmission.

BENEFITS

- Excellent oxidation stability, which has been proven in the results of the oxidation tests on General Motors, Ford, Mercedes Benz and transmissions ZF.

- Superior friction control, as required by Dexron® IID specifications, resulting in a satisfactory operation over the life of the vehicle.

APPLICATIONS

Meets the following requirements:

General Motors DEXRON IIIH
General Motors DEXRON IIIG
General Motors DEXRON IID
General Motors Type A Suffix A (TASA)
Ford MERCON.
Allison TES 389

CHARACTERISTICS

TESTS	TEST METHOD	TYPICAL VALUE
Color	Visual	Red
Appearance	Visual	Clear and bright
Density @20°C, g/ml	ASTM D4052	0.86
Kinematic Viscosity @40°C, cSt	ASTM D445	36
Kinematic Viscosity @100°C, cSt	ASTM D445	7.4
Viscosity Index	ASTM D2270	169
Flash point, °C	ASTM D92	220

Typical Characteristics are those obtained with normal tolerance of production and no constitute a specification. Variations that do not affect the yield product during the normal manufacturing and on different mixing locations are expected.

Information contained in this document is held to changes without previous advisement. The availability of the products could vary depending on the location. For further information, contact venta@lubral.com