

LUBRAL ATF DX VI

AUTOMATIC TRANSMISSION FLUID

DESCRIPTION

Lubricating oil carefully formulated with synthetic base oils and high-tech additives for maximum performance in automatic transmissions that require an oil that meets DEXRON® VI requirements.

BENEFITS

- Improves the performance of old and new GM transmissions.
- Long fluid life at high operating temperatures.
- Excellent oxidation stability under severe conditions.
- Reduces the formation of sludge, lacquer and varnish.

- Protects transmission gears and allows them to operate smoothly.
- Protection against poor shifting and vibration for at least twice the life of competitive products.
- Excellent response for cold starts.

APPLICATIONS

It is suitable for use in applications that require the following level of performance:

- DEXRON® VI.
- FORD MERCON® LV.
- JASO 1A LV

CHARACTERISTICS

TESTS	TEST METHOD	TYPICAL VALUE
Color	Visual	Red
Appearance	Visual	Bright
Density @20°C, g/ml	ASTM D4052	0.85
Kinematic viscosity @40°C, cSt	ASTM D445	30.7
Kinematic viscosity @100°C, cSt	ASTM D445	6
Viscosity index	ASTM D2270	145
Copper sheet corrosion	ASTM D130	1b
Foam Tendencies, ml, max.	ASTM D892	
Sequence I		10/0
Sequence II		10/0
Sequence III		10/0

Typical Characteristics are those obtained with normal tolerance of production and no constitute a specification. Variations that do not affect the yield product during the normal manufacturing and on different mixing locations are expected.

Information contained in this document is held to changes without previous advisement. The availability of the products could vary depending on the location. For further information, contact venta@lubral.com