

LUBRAL M4T SAE 5W-40 API SN/JASO MA2

SYNTHETIC OIL FOR 4-STROKE ENGINES

DESCRIPTION

LUBRAL M4T SAE 5W-40 API SN/JASO MA2 is a Synthetic oil, formulated with high technology for the lubrication of motorcycles with 4-stroke gasoline engines with gearbox and clutches (clutch) immersed in oil. It provides the desired friction performance that motorcycles need to prevent slippage in the wet clutch.

BENEFITS

- Provides complete protection throughout the engine and up to the gearbox.
- Control of sludge and deposits.
- Control of wear caused by the high temperatures and excessive friction to which engines of this type are subjected.

- Anti-rust protection to minimize viscosity increase and the formation of sludge, lacquers and varnishes.

SPECIFICATIONS

- API SN
- JASO MA2 (T903:2016)

APPLICATIONS

LUBRAL M4T SAE 5W-40 API SN/JASO MA2 oil is recommended for the service of 4-stroke gasoline engines of motorcycles with gearbox and clutches (clutch), immersed in oil.

CHARACTERISTICS

TESTS	TEST METHOD	TYPICAL VALUE
SAE Grade	J300	5W-40
Appearance	Visual	Bright
Color	ASTM D1500	2.5
Density @ 20°C, g/cm ³	ASTM D4052	0.86
Kinematic Viscosity @ 40 °C, cSt	ASTM D445	92
Kinematic Viscosity @ 100 °C, cSt	ASTM D445	14
Viscosity Index	ASTM D2270	158
Flash Point COC, °C	ASTM D92	228
Pour Point, °C, max	ASTM D97	-30
Cold Cracking Simulator CSC, cP @-30°C, max	ASTM D5293	6600

Typical Characteristics are those obtained with normal tolerance of production and no constitute a specification. Variations that do not affect the yield product during the normal manufacturing and on different mixing locations are expected. Information contained in this document is held to changes without previous advisement. The availability of the products could vary depending on the location. For further information, contact venta@lubral.com