

# LUBRAL M2T AIR JASO FB/API TC

## AIR-COOLED ENGINE OIL

### DESCRIPTION

Oil made with refined mineral oils and a package of additives that reduces wear of moving parts, reduces the formation of sludge and carbon deposits thus avoiding ignition problems being essential characteristics for use in two-stroke internal combustion engines subject to extreme operating conditions.

It is formulated to be mixed with the fuel in a 20:1 ratio where lubrication is carried out by the evaporation of the fuel that deposits the oil on the cylinder walls, thus providing the necessary protection and lubrication for its operation.

### BENEFITS

- Low ash detergent oil.
- High control of deposits and sludge.
- High wear control.
- High detergent dispersant index.
- Protection against oxidation and rust.
- Reduces pre-ignition and clogging.

### APPLICATIONS

Recommended for two-cycle air-cooled engines, such as motorcycles, mowers, chain saws, lighting plants, generators, leaf blowers, portable implements, rip saws, etc.

Meets or exceeds the following requirements:

- JASO FB
- API TC

### CHARACTERISTICS

TESTS	TEST METHOD	TYPICAL VALUE
Appearance	Visual	Bright
Color	ASTM D1500	2.5
Density @ 20°C, g/cm <sup>3</sup>	ASTM D4052	0.87
Kinematic Viscosity @ 40 °C, cSt	ASTM D445	59
Kinematic Viscosity @ 100 °C, cSt	ASTM D445	8
Viscosity Index	ASTM D2270	113
Flash Point COC, °C	ASTM D92	80
Pour Point, °C, max	ASTM D97	-12

Typical Characteristics are those obtained with normal tolerance of production and no constitute a specification. Variations that do not affect the yield product during the normal manufacturing and on different mixing locations are expected.

Information contained in this document is held to changes without previous advisement. The availability of the products could vary depending on the location. For further information, contact [venta@lubral.com](mailto:venta@lubral.com)