

1510312 Emisión: 02-2020 REV0 IN-IEC-F-05-REV2-07 DE JUNIO DE 2021

LUBRAL M2T TC-W3 50:1

WATER-COOLED ENGINE OIL

DESCRIPTION

This oil is made from refined mineral oils and a low ash additive package that reduces wear on moving parts.

BENEFITS

- Protects against scratching.
- · Avoid the rings sticking.
- · Keeps clean the engine.
- · Good antifriction and lubricity.

APPLICATIONS

TC-W3 50: 1 2-stroke oil is especially recommended for water-cooled 2-cycle marine engines.

It exceeds the recommendations of the most important manufacturers of water-cooled 2-cycle engines, such as MERCURY, JOHNSON, EVINRUDE, YAMAHA, SUZUKI, etc.

It can also be applied on chain saws, motorcycles, lawn mowers, water scooters, etc.

SPECIFICATIONS

Certified TC-W3 (NMMA): RL-30065B

CHARACTERISTICS

TESTS	TEST METHOD	TYPICAL VALUE
NMMA Category service		TC-W3
Appearance	Visual	Bright
Color	Visual	Green
Density @20°C, g/ml	ASTM D1298	0.87
Flash point COC, °C	ASTM D92	90
Kinematic viscosity @ 100 °C, cSt	ASTM D445	5.7
Kinematic viscosity @ 40 °C, cSt	ASTM D445	31
Viscosity Index	ASTM D2270	126
Resistance to rust formation	ASTM D665	Pass

Typical Characteristics are those obtained with normal tolerance of production and no constitute a specification. Variations, that do not affect the yield product during the normal manufacturing and on different mixing locations are expected.

Information contained in this document is held to changes without previous advisement. The availability of the products could vary depending on the location. For further information, contact venta@lubral.com.

