

LUBRAL BF DOT-3

DESCRIPTION

Product resulting from years of research and development, designed for vehicles with hydraulic disc, drum and mixed brake systems, for both light and heavy jobs.

Its advanced formula protects against corrosion, the formation of residues and deposits on metal parts.

It has great chemical stability that allows safer breaking.

BENEFITS

- Protection against corrosion and oxidation of metals present in the hydraulic system.
- High boiling point, which allows the fluid to perform optimally at demanding operating temperatures.
- Compatible with rubber and hydraulic circuit seals.
- Protects metals and rubber.
- Excellent freezing point.

RECOMMENDATIONS

- Follow the vehicle manufacturer's recommendations.
- Contamination with dust, water, petroleum products, or other materials can cause brake system failure.
- Store brake fluid in its original container, keep container clean and closed to prevent moisture absorption.
- Caution: destroy the empty container, do not fill it with liquid or other products.
- This product is dangerous if swallowed, do not leave it within the reach of children.
- Avoid spilling liquid on bullets or vehicle paint.

APPLICATIONS

Meets the requirements:

- NOM-113-SCFI-1995
- SAE J1703
- FMVSS-116 DOT 3

CARACTERÍSTICAS TÍPICAS

PRUEBA	VALOR TÍPICO
Dry equilibrium reflux boiling point, ° C	240
Wet equilibrium reflux boiling point, ° C	148
Kinematic Viscosity @ -40°C cSt	1300
Kinematic Viscosity @ 100°C cSt	1.7
pH	9

Typical Properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are expected during normal manufacturing and at different mixing locations.

The information in this document is subject to change without notice. Product availability may vary depending on the location. For more information, you can contact us at venta@lubral.com