

LUBRAL LIQUIDO PARA DIRECCIÓN HIDRÁULICA

DESCRIPTION

Lubricating oil made with refined mineral base oils, mixed with selected additives that provide the final product with characteristics of resistance to oxidation, corrosion, rust, wear, formation of sludge and deposits, antifoam properties and good stability to shear.

- Good performance at low temperatures.
- Oxidation resistance.
- Avoids rust and corrosion formation.
- High viscosity index.
- Prevents sludge and deposits formation.
- Compatible with other power steering fluids.
- Reduces friction in steering components.

BENEFITS

- Excellent antiwear protection.
- Good antifoam properties.
- Excellent shear stability.

APPLICATIONS

Recommended for vehicles, trucks and Passenger cars.

CHARACTERISTICS

TESTS	TEST METHOD	TYPICAL VALUES
Color	ASTM D1500	1.5
Appearance	Visual	Bright
Flash point COC °C	ASTM D92	180
Kinematic viscosity @ 40°C cSt	ASTM D445	51
Kinematic viscosity @ 100°C cSt	ASTM D445	9
Viscosity Index	ASTM D2270	153
Pour point, °C	ASTM D97	-42
Rust test	ASTM D665	Pass

Typical Characteristics are those obtained with normal tolerance of production and no constitute a specification. Variations that do not affect the yield product during the normal manufacturing and on different mixing locations are expected.

Information contained in this document is held to changes without previous advisement. The availability of the products could vary depending on the location. For further information, contact venta@lubral.com