

LUBRAL SPIN FLUID ISO 15

SPINDLE FLUID

DESCRIPTION

Lubricating oil made from selected paraffinic base oils and additives that provide resistance to oxidation, rust, corrosion, emulsion, wear, extreme pressure and deposit control characteristics.

BENEFITS

- High viscosity index.
- Resistance to corrosion and rust.
- Control over the foam.
- Resistance to wear and extreme pressure.
- Good demulsibility.
- Adequate heat dissipation.

APPLICATIONS

Oil recommended for the lubrication of high-speed spindles of textile machines and tools in which the use of oils inhibited against oxidation and corrosion, precision mechanisms and devices is specified, another application is its use in hydraulic systems or equipment, recommended for sensitive instruments such as telescopes, laboratory equipment, etc.

CHARACTERISTICS

TESTS	TEST METHOD	TYPICAL VALUE
ISO Viscosity Grade		15
Color	ASTM D1500	1.5
Appearance	Visual	Brilliant
Density @20°C, g/ml	ASTM D1298	0.88
Kinematic Viscosity @40°C, cSt	ASTM D445	15
Flash Point COC, °C	ASTM D92	180
Resistance To Rust Formation	ASTM D665	Pass

Typical Properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are expected during normal manufacturing and at different mixing locations.

The information in this document is subject to change without notice. Product availability may vary depending on the location. For more information, you can contact us at venta@lubral.com