

LUBRAL SPIN FLUID ISO 22

SPINDLE FLUID

DESCRIPTION

Lubricating oil made from selected paraffinic base oils and additives that provide resistance to oxidation, rust, corrosion, emulsion, wear, extreme pressure and deposit control characteristics.

BENEFITS

- High viscosity index.
- Resistance to corrosion and rust.
- Control over Foaming.
- Resistance to wear and extreme pressure.
- Good demulsibility.
- Adequate heat dissipation.

APPLICATIONS

Recommended oil for the lubrication of high-speed spindles of textile machines and tools in which the use of oils inhibited against oxidation and corrosion, mechanisms and precision devices is specified, another application is its use in hydraulic systems or equipment, recommended for sensitive instruments such as telescopes, laboratory equipment, etc.

CHARACTERISTICS

TESTS	TEST METHOD	TYPICAL VALUE
ISO Viscosity Grade		22
Color	ASTM D1500	1.0
Appearance	Visual	Brilliant
Density @20°C, g/ml	ASTM D1298	0.86
Kinematic Viscosity @40°C	ASTM D445	22
Flash Point COC, °C	ASTM D92	185
Resistance To Rust Formation	ASTM D665	Pass

Typical Properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are expected during normal manufacturing and at different mixing locations.

The information in this document is subject to change without notice. Product availability may vary depending on the location. For more information, you can contact us at venta@lubral.com