

LUBRAL ROCK DRILL 5

LUBRICANT FOR PNEUMATIC EQUIPMENT

DESCRIPTION

Lubricating oils made with highly refined base oils and additives that give them characteristics of high resistance to wear, extreme pressure, oxidation, rust and corrosion.

- Resistance to wear and extreme pressure
- Suitable lubricity for every application
- Avoid foaming
- Good water repellency

BENEFITS

- Viscosity suitable for pneumatic equipment
- Resistance to oxidation

APPLICATIONS

Recommended for lubricating pneumatic tools and equipment such as: Rotary hammers, rock drills, concrete breakers and other pneumatic equipment.

CHARACTERISTICS

TEST	TEST METHOD	TYPICAL VALUE
ISO Viscosity Grade	-	460
Appearance	Visual	Bright
Color	ASTM D1500	3.5
Density @ 20°C, g/ml	ASTM D4052	0.90
Kinematic Viscosity @ 40°C, cSt	ASTM D445	414
Kinematic Viscosity @ 100°C, cSt	ASTM D445	29
Viscosity Index	ASTM D2270	95
Flash Point COC, °C, min.	ASTM D92	240
Pour Point, °C, max.	ASTM D97	-12
Foam Tendencies, ml	ASTM D892	-
Sequence I	ASTM D892	0/0
Sequence II	ASTM D892	0/0
Sequence III	ASTM D892	0/0

Typical Characteristics are those obtained with normal tolerance of production and no constitute a specification. Variations that do not affect the performance of the product during the normal manufacturing and on different mixing locations are expected. Information contained in this document is held to changes without previous advisement. The availability of the products could vary depending on the location. For further information, contact venta@lubral.com