

DESMOLDANTE PARA CONCRETO

DESCRIPTION

Mixture of mineral oils and refined solvents with polar additives to improve the release action of metal / wood / plastic parts with concrete.

BENEFITS

- High performance concrete release agent.
- Due to its additive's nature, it remains between surfaces facilitating release.
- The release agent is inert to surfaces and materials commonly used in construction so it does not stain, and it could be cleaned easily.
- Improves finishes.
- Quick and clean application.
- Prolongs falsework life.

- Facilitates used material clean such as falsework.

APPLICATION

Product to be used undiluted directly on the falsework using a sprinkler or brush and let dry.

It can be applied immediately before casting or several days before placing the falsework, taking care not to expose the falsework to dust, rain or excessive heat. Although it can be applied to wooden falsework, performance on this type of falsework could be affected. It facilitates the stripping, since it prevents the adherence of concrete and mortar in metal forms and plastic caissons. Improves finishes and does not stain concrete.

CHARACTERISTICS

TESTS	TEST METHOD	TYPICAL VALUE
Color	Visual	Amber
Appearance	Visual	Bright
Relative Density @15.6°C	ASTM D1298	0.87
Flash point, °C	ASTM D92	80
Pour point, °C	ASTM D97	-25

Typical Characteristics are those obtained with normal tolerance of production and no constitute a specification. Variations that do not affect the yield product during the normal manufacturing and on different mixing locations are expected.

Information contained in this document is held to changes without previous advisement. The availability of the products could vary depending on the location. For further information, contact venta@lubral.com