

1510364

Emisión: 02-2020 Rev - 01 062021

### IN - EIC - F - 05 - REV1 - 24 DE FEBRERO DE 2020

# **LUBRAL LITHIUM EP 0**

#### **DESCRIPTION**

High quality, extreme pressure grease for multiple uses, made from Lithium soap (Lithium Hydroxystearate), highly refined mineral oils and additives that allow its application where a grease that supports high impact loads is required. resistance to water washout, corrosion and rust.

#### **BENEFITS**

- · Oxidation and corrosion resistance
- Good pumpability
- · Excellent mechanical stability
- Good water washout resistance
- Extreme pressure and high shock loads resistance
- · Excellent protection against wear

## **APPLICATIONS**

Recommended for the lubrication of bearings, treads, and sliding surfaces operating under normal to severe service conditions. It is especially recommended where loads are high, including occasional shocks due to overloading of equipment. Due to its texture and excellent pumpability, it is recommended for centralized systems, due to its high resistance to water washout, it is recommended in applications where the equipment is exposed to water contamination and it can also be applied in gearboxes when operating conditions and design allow it.

They are applied in the lubrication of tractors, rolling mills, transfer tables, mining equipment, paper plants, breakers or material shredders, among others.

#### **CHARACTERISTICS**

TESTS	TEST METHOD	TYPICAL VALUE
NLGI Grade	ASTM D217	0
Thickener	ASTM D128	Lithium
Color	Visual	Amber
Texture	Visual	Buttery
Worked Penetration @ 60 golpes 1/10 mm 25 °C	ASTM D217	360
Dropping point, °C	ASTM D2265	180
4 balls Weld point, Kg	ASTM D2596	250

Typical Characteristics are those obtained with normal tolerance of production and no constitute a specification. Variations, that do not affect the yield product during the normal manufacturing and on different mixing locations are expected.

Information contained in this document is held to changes without previous advisement. The availability of the products could vary depending on the location. For further information, contact <a href="mailto:venta@lubral.com">venta@lubral.com</a>

