

LUBRAL LITHIUM EP 3

LUBRICATING GREASE

DESCRIPTION

Lubricating grease made with mineral base oils, lithium 12-hydroxystearate thickener, R&O and EP additives that provides a good performance in multipurpose applications such as automotive and industry.

BENEFITS

- Good pumpability
- Multipurpose capacity
- Extreme pressure capabilities

- Rust and oxidation preventing characteristics.
- Water washout resistance

APPLICATIONS

Lubrication of automotive, agriculture and industrial bearings, water pumps, universal joints, chassis for passenger trucks, buses, tractors and mobile construction equipment and in general where a lithium base grease with extreme pressure, oxidation and corrosion resistance characteristics are required.

CHARACTERISTICS

TEST	TEST METHOD	TYPICAL RESULTS
NLGI Grade	ASTM D217	3
Thickener	ASTM D128	Lithium
Color	Visual	Amber
Texture	Visual	Buttery
Worked Penetration @ 25°C, mm/10	ASTM D217	225
Dropping Point, °C	ASTM D2265	190
Water washout @ 79 °C, % weight loss, máx.	ASTM D1264	5
Leakage tendencies, gr, máx	ASTM D1263	5
4 Ball Weld Point, Kgf	ASTM D2596	250

Typical Characteristics are those obtained with normal tolerance of production and no constitute a specification. Variations, that do not affect the yield product during the normal manufacturing and on different mixing locations are expected.

Information contained in this document is held to changes without previous advisement. The availability of the products could vary depending on the location. For further information, contact venta@lubral.com