

LUBRAL COPPER CSX 2000 MAX (ANTI-SEIZE) NLGI 2

CALCIUM SULFONATE GREASE

DESCRIPTION

Copper CSX 2000 MAX 2 is an extreme pressure grease enhanced with solid lubricants as copper and graphite for extreme duty use, has excellent performance in corrosive environments of salt water and ensures protection because of the solid film formation in metal surfaces.

BENEFITS

- High dropping point.
- Cohesive adhesive

- Water resistance
- Workload capacity.

APPLICATION

Copper CSX 2000 MAX is a lubricant grease designed for heavy loaded operations in construction or mining. It is fortified with solid copper and graphite, allowing anti-seize applications.

CHARACTERISTICS

TESTS	TEST METHOD	TYPICAL VALUE
NLGI grade	ASTM D217	2
Thickener	ASTM D128	Calcium sulfonate
Color	Visual	Copper dark
Worked penetration 60 strokes @ 25°C, 1/10 mm	ASTM D217	280
Dropping point, °C	ASTM D2265	300
Water washout, % loss		1 máx.
Base oil viscosity @ 40 °C cSt	ASTM D445	460
Timken OK load, Lbs	ASTM D2509	60
4 ball weld point, Kg	ASTM D2596	620

Typical Characteristics are those obtained with normal tolerance of production and no constitute a specification. Variations, that do not affect the yield product during the normal manufacturing and on different mixing locations are expected. Information contained in this document is held to changes without previous advisement. The availability of the products could vary depending on the location. For further information, contact venta@lubral.com.