

## LUBRAL CALCIUM CHASSIS

### DESCRIPTION

Calcium soap grease, of mild consistency and medium fiber, made with refined mineral oils and additives that provide resistance to rust, corrosion, oxidation and humidity as well as adhesiveness.

### BENEFITS

- Moisture and water washout resistance.
- Good adhesiveness
- Avoids rust and corrosion formation

### APPLICATIONS

It is recommended to lubricate the different parts of the chassis of automotive units such as terminals, ball joints and the fifth wheel. It is also recommended for the lubrication of bearings of some industrial equipment, where there is constant contamination with water such as pumps, outdoor equipment, uncovered gears, among others such as bicycle bearings. It has a low dropping point so it should not be applied in mechanisms that work at more than 65 ° C.

### CHARACTERISTICS

TESTS	TEST METHOD	TYPICAL VALUE
NLGI Grade	ASTM D217	2
Thickener	ASTM D128	Calcium
Color	Visual	Amber
Texture	Visual	Fibrous
Worked penetration @ 60 strokes 1/10 mm 25°C	ASTM D217	280
Dropping point, °C	ASTM D2265	100
Base oil viscosity @ 40°C, cSt	ASTM D445	320

Typical Characteristics are those obtained with normal tolerance of production and no constitute a specification. Variations, that do not affect the yield product during the normal manufacturing and on different mixing locations are expected.

Information contained in this document is held to changes without previous advisement. The availability of the products could vary depending on the location. For further information, contact [venta@lubral.com](mailto:venta@lubral.com).